


Bus
SOR LH 9,5
Coach





type	SOR LH 9,5		Coach
parameters	length	mm	9 630
	width	mm	2 525
	height	mm	3 275
	axle base	mm	4 450
	front overhang	mm	2 380
	rear overhang	mm	2 800
	body	number of doors	
front door width		mm	810
back door width		mm	660
get on height		mm	340
front floor height		mm	1000
luggage space		m ³	5,2
weight		operating	kg
	max. techn. acceptable	kg	15 000
capacity	for sitting		35
	for standing		-
	total		35
properties	design speed	km/h	100
	outer contour radius	mm	8 800
	approach angle	°	9
	departure angle	°	9
engine	Iveco Tector F4AE3682F		185 kW / 850 Nm EURO 5
transmission	ZF 6S 1010 B0		manual 6+1 / 6,72-0,79 R6,03
retarder	Voith R 120		hydraulic
front axle	SOR C 004		independent suspension
rear axle	Meritor RS24-147E		solid, single stage reduction, i=3,73
suspension	pneumatic		pulsating springs; front 2 / back 4
shock-absorber	Brano		fluid, front 2 / back 4
wheels	tires		285 / 70- R19,5
	disc		19,5x7,5"
brakes	Knorr SN6		disc, air-controlled
ABS/ASR	Wabco		system 4S/4M, version E
steering	RBL C 500V		hydraulic compact
independent heating	Eberspaecher Hydronic 24		oil, power 24 kW
wiring	standard		electric vehicle equipment
	CAN-bus SAE 1939		communication to vehicle electronic systems
batteries	Varta		24V / 170 Ah
air-conditioning	Carrier-Sútrak AC 518		18 kW
optional accessories			- electronic control of suspension Wabco ECAS - automatic transmission ZF 6S 1010 B0 - DVD, LCD, coffee machine, icebox, passenger seat

The manufacturer reserves the right to change the specifications without prior notice.

Bus
SOR LH 9,5
 Coach